## **SM-14 Densitometer**Reads densities directly from film viewers

Measuring Aperture 3mm

Measuring Range 0.00 to 4.00 D Accuracy ± 0.02 D or 1%

Repeatability ± 0.02 D Warm-up Time None

Portable Power Source (1) 9v Alkaline Battery Included

Weight 5.9oz. (167.2 grams)

Dimensions 2.5"H(6.35cm)

1.5"W(3.81cm) 4.75"L(12.06cm)



**ESECO** - Speedmaster® has been designing and manufacturing X-ray, photographic, and graphic arts equipment since 1956. All ESECO products have a one year **No Hassle** warranty. Our products are made and serviced in the USA, backed by forty five years of technical experience.

The Speedmaster® SM-14 is accurate to +/- .02 from 0.00 to 4.00 Optical Density. The push button switch "wakes up" the Pocket Pal to give a stable reading in just 1 second. Simply place film on your viewer, put the SM-14's "EASY READ" probe on the area to be read then push the read button.

The *Speedmaster® SM-14* is constructed for rugged and durable use, minimal drift and no warm-up time, providing it with fast dependable readings. Reliability and ease of use make the compact *Speedmaster® SM-14 "Pocket Pal"* the ideal cost-effective choice for film quality assurance.